



# jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980  
 OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800  
 FAX 845-947-1712

## **J**® STYLES 1429, 1430, & 1431; CSA (XLPVC)

**DESCRIPTION:** CROSS LINKED PVC INSULATED GENERAL PURPOSE ELECTRONIC HOOK-UP WIRE RESISTANT TO CUT-THROUGH, ABRASION, WATER, OIL, ACIDS, SOLVENTS, AND FUNGUS. RESISTS SHRINK BACK AND DEFORMATION WHEN IN DIRECT CONTACT WITH A SOLDERING IRON. DESIGNED FOR INTERNAL WIRING OF APPLIANCES.

**SPECIFICATIONS:** UL-VW1; CSA XLPVC

**CONDUCTOR:** STRANDED OR SOLID TINNED COPPER.\*

**TEMPERATURE RATING:** STYLE 1429 (CSA 14444) 80°C; STYLE 1430 (CSA REW) 105°C; STYLE 1431 (CSA REW) 105°C.

**VOLTAGE RATING:** STYLE 1429 150 VOLTS R.M.S.; STYLE 1430 300 VOLTS R.M.S.; STYLE 1431 600 VOLTS R.M.S.

**STANDARD SPOOL PUT-UP:** 1000 FT, 5000 FT.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO. AND COLOR.

AWG SIZE	STRAND	J® STYLE 1429		J® STYLE 1430		J® STYLE 1431	
		CATALOG #	O.D. (in.)	CATALOG #	O.D. (in.)	CATALOG #	O.D. (in.)
30	7X38	JXVB-3007	.033				
28	SOLID	JXVB-2801	.035				
28	7X36	JXVB-2807	.036				
26	SOLID	JXVB-2601	.038				
26	7X34	JXVB-2607	.040	JXVC-2607	.053	JXVD-2607	.083
26	19X38	JXVB-2619	.040	JXVC-2619	.053		
24	SOLID	JXVB-2401	.042	JXVC-2401	.054		
24	7X32	JXVB-2407	.044	JXVC-2407	.058	JXVD-2407	.088
24	19X36	JXVB-2419	.044	JXVC-2419	.058		
22	SOLID	JXVB-2201	.047	JXVC-2201	.058		
22	7X30	JXVB-2207	.051	JXVC-2207	.064	JXVD-2207	.094
22	19X34	JXVB-2219	.051	JXVC-2219	.064		
20	SOLID	JXVB-2001	.054	JXVC-2001	.065		
20	7X28	JXVB-2007	.059	JXVC-2007	.072		
20	19X32	JXVB-2019	.059	JXVC-2019	.072	JXVD-2019	.103
18	SOLID	JXVB-1801	.062	JXVC-1801	.072		
18	7X26	JXVB-1807	.068	JXVC-1807	.082		
18	19X30	JXVB-1819	.068	JXVC-1819	.082	JXVD-1819	.111
16	19X.0117	JXVB-1619	.080	JXVC-1619	.090	JXVD-1619	.120
14	19X.0147					JXVD-1419	.134
12	19X.0186					JXVD-1219	.153
10	37X.0168					JXVD-1037	.177
8	133X29					JXVD-8133	.263
6	133X27					JXVD-6133	.343
4	133X25					JXVD-4133	.399
2	665X30					JXVD-2665	.457
1	817X30					JXVD-1817	.540
1/0	1045X30					JXVD-X01045	.575
2/0	1330X30					JXVD-X21330	.635
3/0	1672X30					JXVD-X31672	.695
4/0	2109X30					JXVD-X42109	.750

\*BARE COPPER AND ADDITIONAL STRANDINGS AVAILABLE, CONSULT FACTORY.