



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

TYPE-EE PTFE INSULATED WIRE

DESCRIPTION: UNPRINTED PTFE INSULATED HOOK-UP WIRE, CONFORMING TO MIL-W-16878/5C IN AWG SIZES 32-6 IN THE STRANDINGS SPECIFIED AND REPLACING MIL-W-16878 TYPE EE FOR COMMERCIAL USE.

SPECIFICATIONS: NEMA HP 3 AND MIL-W-16878/5.

CONDUCTOR: STRANDED OR SOLID SILVER PLATED COPPER.

INSULATION: PTFE, .015".

TEMPERATURE RATING: -65°C TO +200°C.

VOLTAGE RATING: 1000 VOLTS R.M.S.

STANDARD SPOOL PUT-UP: 1000 FT., 5000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	DESIGNATION		SILVER PLATED COPPER		O.D. (inches)	
	NEMA HP 3	MIL-W-16878/5	AWG SIZE	STRAND	MIN.	MAX.
JEE3201	EE32-1-HP3	BAA	32	SOLID	.034	.042
JEE3207	EE32-7-HP3	BAB	32	7X40	.036	.044
JEE3219	EE32-19-HP3		32	19X44	.036	.044
JEE3001	EE30-1-HP3	BBA	30	SOLID	.036	.044
JEE3007	EE30-7-HP3	BBB	30	7X38	.038	.046
JEE3019	EE30-19-HP3		30	19X42	.038	.046
JEE2801	EE28-1-HP3	BCA	28	SOLID	.039	.047
JEE2807	EE28-7-HP3	*	28	7X36	.041	.049
JEE2819	EE28-19-HP3		28	19X40	.041	.049
JEE2601	EE26-1-HP3	BDA	26	SOLID	.042	.050
JEE2607	EE26-7-HP3	BDB	26	7X34	.045	.053
JEE2619	EE26-19-HP3	*	26	19X38	.045	.053
JEE2401	EE24-1-HP3	BEA	24	SOLID	.046	.054
JEE2407	EE24-7-HP3	BEB	24	7X32	.050	.058
JEE2419	EE24-19-HP3	*	24	19X36	.050	.058
JEE2201	EE22-1-HP3	BFA	22	SOLID	.051	.059
JEE2207	EE22-7-HP3	BFB	22	7X30	.056	.064
JEE2219	EE22-19-HP3	*	22	19X34	.056	.064
JEE2001	EE20-1-HP3	BGA	20	SOLID	.058	.066
JEE2007	EE20-7-HP3	BGB	20	7X28	.064	.072
JEE2019	EE20-19-HP3	*	20	19X32	.064	.072
JEE1801	EE18-1-HP3	BHA	18	SOLID	.066	.076
JEE1807	EE18-7-HP3	BHB	18	7X26	.074	.084
JEE1819	EE18-19-HP3	*	18	19X30	.074	.084
JEE1601	EE16-1-HP3	BJA	16	SOLID	.077	.089
JEE1619	EE16-19-HP3	*	16	19X29	.083	.095
JEE1419	EE14-19-HP3	*	14	19X27	.098	.114
JEE1219	EE12-19-HP3	*	12	19X25	.117	.133
JEE1237	EE12-37-HP3	BLG	12	37X28	.115	.131
JEE1037	EE10-37-HP3	*	10	37X26	.137	.153
JEE8133	EE8-133-HP3	*	8	133X29	.199	.219
JEE6133	EE6-133-HP3	BPL	6	133X27	.253	.273.

*DELETED FROM MIL-W-16878/5 AND REPLACED BY MIL-W-22759/9B