



# jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980  
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800  
FAX 845-947-1712

## MIL-W-22759/9 PTFE INSULATED WIRE

**DESCRIPTION:** PRINTED PTFE INSULATED HOOK-UP WIRE, CONFORMING TO MIL-W-22759/9 IN AWG SIZES 28-8 IN THE STRANDINGS SPECIFIED AND REPLACING MIL-W-16878/5C.

**SPECIFICATION:** MIL-W-22759/9.

**TEMPERATURE RATING:** -65°C TO 200°C.

**CONDUCTOR:** STRANDED SILVER PLATED COPPER.

**VOLTAGE RATING:** 1000 VOLTS R.M.S.

**INSULATION:** PTFE, .015".

**STANDARD SPOOL PUT-UP:** 1000 FT.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION	SILVER PLATED COPPER		RESISTANCE@20°C Ω/1000 FT MAX	O.D. (inches)	
		AWG SIZE	STRAND		MIN.	MAX.
J9EE-2807	M22759/9-28	28	7X36	63.8	.041	.045
J9EE-2619	M22759/9-26	26	19X38	38.4	.046	.050
J9EE-2419	M22759/9-24	24	19X36	24.3	.051	.055
J9EE-2219	M22759/9-22	22	19X34	15.1	.058	.062
J9EE-2019	M22759/9-20	20	19X32	9.19	.066	.070
J9EE-1819	M22759/9-18	18	19X30	5.79	.076	.080
J9EE-1619	M22759/9-16	16	19X29	4.52	.083	.087
J9EE-1419	M22759/9-14	14	19X27	2.88	.097	.103
J9EE-1219	M22759/9-12	12	19X25	1.81	.116	.124
J9EE-1037	M22759/9-10	10	37X26	1.19	.137	.145
J9EE-8133	M22759/9-8	8	133X29	.658	.202	.212

## MIL-W-22759/11 PTFE INSULATED WIRE

**DESCRIPTION:** PRINTED PTFE INSULATED HOOK-UP WIRE, CONFORMING TO MIL-W-22759/11 IN AWG SIZES 28-8 IN THE STRANDINGS SPECIFIED AND REPLACING MIL-W-16878/4C.

**SPECIFICATION:** MIL-W-22759/11.

**TEMPERATURE RATING:** -65°C TO 200°C.

**CONDUCTOR:** STRANDED SILVER PLATED COPPER.

**VOLTAGE RATING:** 600 VOLTS R.M.S.

**INSULATION:** PTFE, .010".

**STANDARD SPOOL PUT-UP:** 1000 FT.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION	SILVER PLATED COPPER		RESISTANCE@20°C Ω/1000 FT MAX	O.D. (inches)	
		AWG SIZE	STRAND		MIN.	MAX.
J11E-2807	M22759/11-28	28	7X36	63.8	.031	.035
J11E-2619	M22759/11-26	26	19X38	38.4	.036	.040
J11E-2419	M22759/11-24	24	19X36	24.3	.041	.045
J11E-2219	M22759/11-22	22	19X34	15.1	.047	.051
J11E-2019	M22759/11-20	20	19X32	9.19	.056	.060
J11E-1819	M22759/11-18	18	19X30	5.79	.066	.070
J11E-1619	M22759/11-16	16	19X29	4.52	.073	.077
J11E-1419	M22759/11-14	14	19X27	2.88	.088	.092
J11E-1219	M22759/11-12	12	19X25	1.81	.108	.114
J11E-1037	M22759/11-10	10	37X26	1.19	.135	.143
J11E-8133	M22759/11-8	8	133X29	.658	.198	.206