



# jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980  
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800  
FAX 845-947-1712

## MIL-W-22759/32 TEFZEL<sup>®</sup> INSULATED WIRE

**DESCRIPTION:** PRINTED<sup>†</sup> TEFZEL<sup>®</sup> INSULATED HOOK-UP WIRE, CONFORMING TO MIL-W-22759/32 IN AWG SIZES 30-12 IN THE STRANDINGS SPECIFIED.

**SPECIFICATION:** MIL-W-22759/32.

**TEMPERATURE RATING:** -65°C TO 150°C.

**CONDUCTOR:** STRANDED TINNED COPPER.

**VOLTAGE RATING:** 600 VOLTS R.M.S.

**INSULATION:** EXTRUDED ETFE.

**STANDARD SPOOL PUT-UP:** 1000 FT.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO, AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION	TINNED COPPER		RESISTANCE@20°C Ω/1000 FT. MAX.	O.D. (inches)	
		AWG SIZE	STRAND		MIN.	MAX.
J32TZ-3007	M22759/32-30	30	7X38	108.4	.022	.026
J32TZ-2807	M22759/32-28	28	7X36	68.6	.025	.029
J32TZ-2619	M22759/32-26	26	19X38	41.3	.030	.034
J32TZ-2419	M22759/32-24	24	19X36	26.2	.035	.039
J32TZ-2219	M22759/32-22	22	19X34	16.2	.041	.045
J32TZ-2019	M22759/32-20	20	19X32	9.88	.048	.052
J32TZ-1819	M22759/32-18	18	19X30	6.23	.058	.062
J32TZ-1619	M22759/32-16	16	19X29	4.81	.066	.070
J32TZ-1419	M22759/32-14	14	19X27	3.06	.082	.088
J32TZ-1237	M22759/32-12	12	37X28	2.02	.100	.106

## MIL-W-22759/34 TEFZEL<sup>®</sup> INSULATED WIRE

**DESCRIPTION:** PRINTED<sup>†</sup> TEFZEL<sup>®</sup> INSULATED HOOK-UP WIRE, CONFORMING TO MIL-W-22759/34 IN AWG SIZES 24-00 IN THE STRANDINGS SPECIFIED.

**SPECIFICATION:** MIL-W-22759/34.

**TEMPERATURE RATING:** -65°C TO 150°C.

**CONDUCTOR:** STRANDED TINNED COPPER.

**VOLTAGE RATING:** 600 VOLTS R.M.S.

**INSULATION:** EXTRUDED ETFE, DOUBLE COATING.

**STANDARD SPOOL PUT-UP:** 1000 FT.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION	TINNED COPPER		RESISTANCE@20°C Ω/1000 FT. MAX.	O.D. (inches)	
		AWG SIZE	STRAND		MIN.	MAX.
J34TZ-2419	M22759/34-24	24	19X36	26.2	.043	.047
J34TZ-2219	M22759/34-22	22	19X34	16.2	.048	.052
J34TZ-2019	M22759/34-20	20	19X32	9.88	.056	.060
J34TZ-1819	M22759/34-18	18	19X30	6.23	.067	.073
J34TZ-1619	M22759/34-16	16	19X29	4.81	.074	.080
J34TZ-1419	M22759/34-14	14	19X27	3.06	.091	.097
J34TZ-1237	M22759/34-12	12	37X28	2.02	.108	.114
J34TZ-1037	M22759/34-10	10	37X26	1.26	.130	.138
J34TZ-8133	M22759/34-8	8	133X29	.701	.187	.203
J34TZ-6133	M22759/34-6	6	133X27	.445	.231	.251
J34TZ-4133	M22759/34-4	4	133X25	.280	.300	.320
J34TZ-2665	M22759/34-2*	2	665X30	.183	.389	.421
J34TZ-1817	M22759/34-1*	1	817X30	.149	.429	.461
J34TZ-X01045	M22759/34-01*	0	1045X30	.116	.469	.501
J34TZ-X21330	M22759/34-02*	00	1330X30	.091	.529	.561

<sup>†</sup>NOT REQUIRED FOR AWG 24 AND SMALLER

\*ADDITIONAL COVER OF TREATED POLYAMIDE BRAID REQUIRED.