



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
 OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
 FAX 845-947-1712

WIRE WRAP, KYNAR® AND TEFZEL®

DESCRIPTION: INSULATED CONDUCTORS FOR SOLDERLESS WIRE WRAP APPLICATIONS. CAN BE USED WITH EITHER AUTOMATED OR HAND WRAPPING TOOLS.

SPECIFICATIONS: UL, MIL-W-81822/3 (KYNAR®), MIL-W-81822/13 (TEFZEL®).

CONDUCTORS: SOLID SOFT SILVER PLATED COPPER.

TEMPERATURE RATING: KYNAR®: UL 105°C; MIL-SPEC 135°C.

TEFZEL®: UL 105°C; MIL-SPEC 150°C.

VOLTAGE RATING: KYNAR®: UL NOT SPECIFIED; MIL-SPEC 300 VOLTS.

TEFZEL®: UL NOT SPECIFIED; MIL-SPEC 300 VOLTS.

STANDARD SPOOL PUT-UP: 1000 FT., 5000 FT., 10000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR.

KYNAR®

AWG SIZE	CATALOG NO.	MILITARY DESIGNATION	NOM. O.D. (inches)	CATALOG NO.	UL STYLE	NOM. O.D. (inches)
30	JMKY-30	MIL-W-81822/3-30	.020	JKY2-30	1422	.021
30				JKY3-30	1423	.020
28	JMKY-28	MIL-W-81822/3-28	.027	JKY2-28	1422	.024
28				JKY3-28	1423	.022
26	JMKY-26	MIL-W-81822/3-26	.030	JKY2-26	1422	.027
26				JKY3-26	1423	.025
24	JMKY-24	MIL-W-81822/3-24	.034	JKY2-24	1422	.032
24				JKY3-24	1423	.030
22	JMKY-22	MIL-W-81822/3-22	.039	JKY2-22	1422	.037
22				JKY3-22	1423	.035
20	JMKY-20	MIL-W-81822/3-20	.046	JKY2-20	1422	.043
20				JKY3-20	1423	.041
18	JMKY-18	MIL-W-81822/3-18	.054			

TEFZEL®

AWG SIZE	CATALOG NO.	MILITARY DESIGNATION	NOM. O.D. (inches)	CATALOG NO.	UL STYLE	NOM. O.D. (inches)
30	JMTZ-30	MIL-W-81822/13-30	.020	JTZ-30	1516/1523	.021
28	JMTZ-28	MIL-W-81822/13-28	.027	JTZ-28	1516/1523	.024
26	JMTZ-26	MIL-W-81822/13-26	.030	JTZ-26	1516/1523	.027
24	JMTZ-24	MIL-W-81822/13-24	.034	JTZ-24	1516/1523	.032
22	JMTZ-22	MIL-W-81822/13-22	.039	JTZ-22	1516/1523	.037
20	JMTZ-20	MIL-W-81822/13-20	.046	JTZ-20	1516/1523	.043
18	JMTZ-18	MIL-W-81822/13-18	.054			