



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

GPT PRIMARY WIRE

DESCRIPTION: FOR GENERAL PURPOSE ORIGINAL EQUIPMENT AND REPLACEMENT WIRING IN MOTOR DRIVEN EQUIPMENT. RESISTANT TO OIL, WATER, ACIDS, ALKALIES, OZONE, GREASE, AND DIESEL FUMES.

CONDUCTOR: 99.9% PURE SOFT BARE ELECTROLYTIC COPPER CONDUCTORS FOR MAXIMUM FLEXIBILITY AND CONDUCTIVITY.

INSULATION: GPT TYPE FLAME RETARDENT FLEXIBLE PVC.

TEMPERATURE RATING: -40°C TO 80°C.

VOLTAGE RATING: 300 VOLTS R.M.S.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR CODE. COLORS ARE: 0-BLACK; 1-BROWN; 2-RED; 3-ORANGE; 4-YELLOW; 5-GREEN; 6-BLUE; 7-PURPLE; 8-GRAY; 9-WHITE.

CATALOG NO.	AWG SIZE	STRAND	NOM. O.D. (inches)	STOCK COLORS	PUT-UPS
JAP18-6000 JAP18-3000 JAP18-1000 JAP18-500	18	16X30	.093	0-9	6000 FT 3000 FT 1000 FT 500 FT
JAP16-5000 JAP16-2500 JAP16-1000 JAP16-500	16	19X29	.105	0-9	5000 FT 2500 FT 1000 FT 500 FT
JAP14-4000 JAP14-2000 JAP14-1000 JAP14-500	14	19X27	.118	0-9	4000 FT 2000 FT 1000 FT 500 FT
JAP12-4000 JAP12-2000 JAP12-1000 JAP12-500	12	65X30	.143	0-9	4000 FT 2000 FT 1000 FT 500 FT
JAP10-3000 JAP10-1000 JAP10-500	10	105x30	.176	0, 2, 4, 5, 9	3000 FT 1000 FT 500 FT
JAP8-1000 JAP8-500	8	96X28	.217	0, 2, 4, 5, 9	1000 FT 500 FT