



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

GPT WIRE

DESCRIPTION: PRINTED POWER DISTRIBUTION CABLE. HIGHLY RESISTANT TO OIL, WATER, ACIDS, ALKALIES, OZONE, GREASE, AND DIESEL FUMES.

CONDUCTOR: 99.9% PURE SOFT BARE FINELY STRANDED ELECTROLYTIC COPPER CONDUCTORS CABLED IN A ROPE LAY DESIGN FOR MAXIMUM FLEXIBILITY AND CONDUCTIVITY, PER ASTM B-172.

INSULATION: GPT TYPE VW-1 FLAME RETARDANT GRADE PVC, WITH A BRIGHT, SUPER SHINY FINISH.

TEMPERATURE RATING: -30°C TO 105°C. **VOLTAGE RATING:** 600 VOLTS R.M.S.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR. AVAILABLE COLORS ARE: RED, BLACK, CLEAR RED, CLEAR BLACK (SMOKE), CLEAR BLUE, CLEAR GREEN, CLEAR GOLD, NEON PINK, NEON GREEN, AND NEON ORANGE.

CATALOG NO.	AWG SIZE	STRAND	NOM. O.D. (inches)	STOCK COLORS	PUT-UPS
JAK10-1000	10	7X59 (413X36)	.230	ALL	1000 FT
JAK10-500					500 FT
JAK10-250					250 FT
JAK10-100					100 FT
JAK8-500	8	7X95 (665X36)	.270	ALL	500 FT
JAK8-250					250 FT
JAK8-100					100 FT
JAK4-500	4	19X88 (1672X36)	.425	ALL	500 FT
JAK4-250					250 FT
JAK4-100					100 FT
JAK2-250	2	19X139 (2641X36)	.500	RED & BLACK	250 FT
JAK2-100					100 FT

2 CON. POLARIZED GPT TYPE ZIP CORD

DESCRIPTION: ONE CONDUCTOR RED AND ONE CONDUCTOR BLACK (FOR POLARITY).

CONDUCTORS: MULTI-STRANDED SOFT BARE ELECTROLYTIC COPPER.

INSULATION: GPT GRADE VW-1 FLAME RETARDANT PVC.

TEMPERATURE RATING: 80°C.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO.

CATALOG NO.	AWG SIZE	STRAND	NOM. O.D. (inches)	PUT-UPS
JAZ18-1000	18	16X30	.100 X .205	1000 FT
JAZ18-500				500 FT
JAZ16-1000	16	26X30	.120 X .245	1000 FT
JAZ16-500				500 FT
JAZ14-1000	14	41X30	.145 X .295	1000 FT
JAZ14-500				500 FT
JAZ12-1000	12	65X30	.160 X .325	1000 FT
JAZ12-500				500 FT
JAZ10-500	10	105X30	.200 X .430	500 FT
JAZ10-250				250 FT
JAZ10-100				100 FT
JAZ8-500				500 FT
JAZ8-250	8	96X28	.240 X .490	250 FT
JAZ8-100				100 FT