



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

2 CONDUCTOR PARALLEL CORDAGE

UL/CSA LISTED CORDAGE

DESCRIPTION: PRIMARILY FOR LAMP CORD WIRES, THESE ITEMS ARE ALSO USED AS SPEAKER EXTENSION CABLES.

CONDUCTORS: SOFT BARE COPPER

INSULATION: UL CLASS 11 60°C VW-1 PVC.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR. STANDARD COLORS ARE WHITE, BROWN, AND BLACK.*

CATALOG NO.	AWG SIZE	UL/CSA TYPE	STRAND	NOM. FINISHED WIRE SIZE (inches)	PUT-UPS
JSP118-1000	18	SPT-1	41X34	.105 X .210	1000 FT
JSP118-500					500 FT
JSP118-250					250 FT
JSP218-1000	18	SPT-2	41X34	.145 X .300	1000 FT
JSP218-500					500 FT
JSP218-250					250 FT
JSP216-1000	16	SPT-2	65X34	.155 X .310	1000 FT
JSP216-500					500 FT
JSP216-250					250 FT

2 CONDUCTOR MINIATURE ZIP CORD

DESCRIPTION: DESIGNED TO MEET THE REQUIREMENTS FOR A MINIATURE ZIP CORD. ORDINARILY SUPPLIED WITHOUT POLARITY IDENTIFICATION, HOWEVER IDENTIFICATION CAN BE SUPPLIED ON REQUEST. FOR 80°C OPERATION.

CONDUCTORS: BARE OR TINNED COPPER

INSULATION: EXTRA SOFT, FLEXIBLE 80°C BLACK PVC INSULATION.*

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO.

CATALOG NO.	AWG SIZE	STRAND	NOM. FINISHED WIRE SIZE (inches)	PUT-UPS
JSW28-7B-1000	28	7X36 BARE	.040 X .082	1000 FT
JSW28-7T-1000	28	7X36 TINNED	.040 X .082	1000 FT
JSW28-19B-1000	28	19X40 BARE	.040 X .082	1000 FT
JSW28-19T-1000	28	19X40 TINNED	.040 X .082	1000 FT
JSW27-48B-1000	27	48X44 BARE	.040 X .082	1000 FT

CONDUCTORS: BARE COPPER - ONE CONDUCTOR WITH TINNED STRANDS FOR POLARITY.

INSULATION: EXTRA SOFT, FLEXIBLE 60°C CLEAR PVC INSULATION.*

CATALOG NO.	AWG SIZE	STRAND	NOM. FINISHED WIRE SIZE (inches)	PUT-UPS
JSW24-1000	24	7X32	.060 X .120	1000 FT
JSW24-500				500 FT
JSW22-1000	22	7X30	.070 X .140	1000 FT
JSW22-500				500 FT

*OTHER COLORS AVAILABLE, CONSULT FACTORY.