



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

TINNED COPPER BUS BAR

DESCRIPTION: SOFT DRAWN ELECTROLYTIC SOLID COPPER, ANNEALED AND TINNED FOR EASY SOLDERING.

SPECIFICATION: QQ-W-343 TYPE S.

CONDUCTOR: SOLID TINNED COPPER.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND PUT-UP.

CATALOG NO.	AWG SIZE	NOM. O.D. (inches)	NOM. O.D. (mm)	CIRCULAR MIL AREA	NOM. WEIGHT LB./1000 FT
JBB-40	40	.0031	.0787	9.610	.0291
JBB-39	39	.0035	.0889	12.25	.0371
JBB-38	38	.0040	.1016	16.00	.0484
JBB-37	37	.0045	.1143	2.25	.0613
JBB-36	36	.0050	.1270	25.00	.0757
JBB-35	35	.0056	.1422	31.36	.0949
JBB-34	34	.0063	.1600	39.69	.1201
JBB-33	33	.0071	.1803	5.41	.1526
JBB-32	32	.0080	.2032	64.00	.1937
JBB-31	31	.0089	.2261	79.21	.2398
JBB-30	30	.0100	.2540	10.0	.3025
JBB-29	29	.0113	.2870	127.7	.3866
JBB-28	28	.0126	.3200	158.8	.4806
JBB-27	27	.0142	.3607	201.6	.6101
JBB-26	26	.0159	.4039	252.8	.7650
JBB-25	25	.0179	.4547	32.4	.9700
JBB-24	24	.0201	.5105	404.0	1.223
JBB-23	23	.0226	.5740	51.8	1.546
JBB-22	22	.0253	.6426	64.1	1.937
JBB-21	21	.0285	.7239	812.3	2.459
JBB-20	20	.0320	.8128	1024	3.099
JBB-19	19	.0359	.9119	1289	3.900
JBB-18	18	.0403	1,024	1624	4.914
JBB-17	17	.0453	1,151	2052	6.213
JBB-16	16	.0508	1,290	2581	7.812
JBB-15	15	.0571	1,450	3260	9.870
JBB-14	14	.0641	1,628	4109	12.44
JBB-13	13	.0720	1,829	5184	15.69
JBB-12	12	.0808	2,052	6529	19.76
JBB-11	11	.0907	2,304	8226	24.90
JBB-10	10	.1019	2,588	10384	31.43
JBB-09	9	.1144	2,906	13087	39.62
JBB-08	8	.1285	3,264	16512	49.98
JBB-07	7	.1443	3,665	20822	63.03
JBB-06	6	.1620	4,115	26244	79.44
JBB-05	5	.1819	4,620	33088	100.2
JBB-04	4	.2043	5,189	41738	126.3
JBB-03	3	.2294	5,827	55624	159.3
JBB-02	2	.2576	6,543	66358	200.9