



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

SHIELDED CABLE – PTFE INSULATION

DESCRIPTION: PTFE INSULATED CONDUCTORS (TYPE E), COLOR CODED, CABLED FOR 2 OR MORE CONDUCTORS, BRAIDED, WITH SILVER PLATED COPPER (90% MINIMUM COVERAGE), WITH A SINTERED TAPE WRAPPED PTFE OR EXTRUDED FEP JACKET OVERALL.

CONDUCTORS: STRANDED SILVER-PLATED COPPER.

INSULATION: PRIMARY - EXTRUDED PTFE. **JACKET -** TAPED PTFE OR EXTRUDED FEP.

TEMPERATURE RATING: -65°C TO 200°C.

VOLTAGE RATING: 600 VOLTS R.M.S.

STANDARD SPOOL PUT-UP: 1000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. SUPPLIED WITH A WHITE JACKET AND THE FOLLOWING COLOR CODE: 1-WHITE; 2-BLACK; 3-RED; 4-GREEN.*

AWG SIZE	NUMBER OF STRAND CONDUCTORS	CATALOG NO. TAPED JACKET	NOM. O.D. (inches)	CATALOG NO. EXTRUDED JACKET	NOM. O.D. (inches)	
30	7x38	1	JSTJ3007-1	.082	JSFJ3007-1	.072
30	7x38	2	JSTJ3007-2	.114	JSFJ3007-2	.104
30	7x38	3	JSTJ3007-3	.120	JSFJ3007-3	.110
28	7x36	1	JSTJ2807-1	.085	JSFJ2807-1	.075
28	7x36	2	JSTJ2807-2	.120	JSFJ2807-2	.110
28	7x36	3	JSTJ2807-3	.127	JSFJ2807-3	.117
26	19X38	1	JSTJ2619-1	.089	JSFJ2619-1	.079
26	19X38	2	JSTJ2619-2	.128	JSFJ2619-2	.118
26	19X38	3	JSTJ2619-3	.136	JSFJ2619-3	.126
26	19X38	4	JSTJ2619-4	.144	JSFJ2619-4	.134
24	19X36	1	JSTJ2419-1	.094	JSFJ2419-1	.084
24	19X36	2	JSTJ2419-2	.138	JSFJ2419-2	.128
24	19X36	3	JSTJ2419-3	.147	JSFJ2419-3	.137
24	19X36	4	JSTJ2419-4	.156	JSFJ2419-4	.146
22	19X34	1	JSTJ2219-1	.100	JSFJ2219-1	.090
22	19X34	2	JSTJ2219-2	.150	JSFJ2219-2	.140
22	19X34	3	JSTJ2219-3	.160	JSFJ2219-3	.150
22	19X34	4	JSTJ2219-4	.170	JSFJ2219-4	.160
20	19X32	1	JSTJ2019-1	.108	JSFJ2019-1	.098
20	19X32	2	JSTJ2019-2	.166	JSFJ2019-2	.156
20	19X32	3	JSTJ2019-3	.178	JSFJ2019-3	.168
20	19X32	4	JSTJ2019-4	.189	JSFJ2019-4	.179
18	19X30	1	JSTJ1819-1	.119	JSFJ1819-1	.109
18	19X30	2	JSTJ1819-2	.188	JSFJ1819-2	.178
18	19X30	3	JSTJ1819-3	.202	JSFJ1819-3	.192
18	19X30	4	JSTJ1819-4	.216	JSFJ1819-4	.206
16	19X29	1	JSTJ1619-1	.130	JSFJ1619-1	.120
16	19X29	2	JSTJ1619-2	.210	JSFJ1619-2	.200
16	19X29	3	JSTJ1619-3	.226	JSFJ1619-3	.216
14	19X27	1	JSTJ1419-1	.145	JSFJ1419-1	.135
14	19X27	2	JSTJ1419-2	.240	JSFJ1419-2	.230
12	19X25	1	JSTJ1219-1	.164	JSFJ1219-1	.154
12	19X25	2	JSTJ1219-2	.278	JSFJ1219-2	.268
10	37X26	1	JSTJ1037-1	.184	JSFJ1037-1	.174

*CONSULT FACTORY FOR OTHER STRANDINGS, COLOR CODES, AND NUMBER OF CONDUCTORS