



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

SHIELDED CABLE MIL-C-27500, TYPE RC - QPL

DESCRIPTION: PTFE INSULATED CONDUCTORS (MIL-W-22759/11), COLOR CODED, CABLED FOR 2 OR MORE CONDUCTORS, BRAIDED WITH SILVER PLATED COPPER WITH A SINTERED POLYTETRAFLUOROETHYLENE JACKET OVERALL. MANUFACTURER'S MARKER TAPE OR CONDUCTOR PRINT UNDER SHIELD IDENTIFIES QPL PRODUCT.

CONDUCTORS: STRANDED SILVER PLATED COPPER.

INSULATION: PRIMARY - EXTRUDED PTFE. **JACKET -** TAPED PTFE.

TEMPERATURE RATING: -55°C TO 200°C.

VOLTAGE RATING: 600 VOLTS R.M.S.

STANDARD SPOOL PUT-UP: 1000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. SUPPLIED WITH A WHITE JACKET AND THE FOLLOWING CONDUCTOR COLOR CODE: 1-WHITE, 2-WHITE/BLUE, 3-WHITE/ORANGE, 4-WHITE/GREEN.*

CATALOG NO.	MILITARY DESIGNATION	AWG SIZE	STRAND	NO. OF COND.	NOMINAL CABLE O.D. (inches)
JMSO6-26RC1	M27500-26RC1SO6	26	19X38	1	.084
JMSO6-26RC2	M27500-26RC2SO6	26	19X38	2	.120
JMSO6-26RC3	M27500-26RC3SO6	26	19X38	3	.130
JMSO6-26RC4	M27500-26RC4SO6	26	19X38	4	.140
JMSO6-24RC1	M27500-24RC1SO6	24	19X36	1	.085
JMSO6-24RC2	M27500-24RC2SO6	24	19X36	2	.140
JMSO6-24RC3	M27500-24RC3SO6	24	19X36	3	.145
JMSO6-24RC4	M27500-24RC4SO6	24	19X36	4	.155
JMSO6-22RC1	M27500-22RC1SO6	22	19X34	1	.095
JMSO6-22RC2	M27500-22RC2SO6	22	19X34	2	.150
JMSO6-22RC3	M27500-22RC3SO6	22	19X34	3	.155
JMSO6-22RC4	M27500-22RC4SO6	22	19X34	4	.165
JMSO6-20RC1	M27500-20RC1SO6	20	19X32	1	.100
JMSO6-20RC2	M27500-20RC2SO6	20	19X32	2	.170
JMSO6-20RC3	M27500-20RC3SO6	20	19X32	3	.175
JMSO6-20RC4	M27500-20RC4SO6	20	19X32	4	.195
JMSO6-18RC1	M27500-18RC1SO6	18	19X30	1	.120
JMSO6-18RC2	M27500-18RC2SO6	18	19X30	2	.190
JMSO6-18RC3	M27500-18RC3SO6	18	19X30	3	.200
JMSO6-18RC4	M27500-18RC4SO6	18	19X30	4	.220
JMSO6-16RC1	M27500-16RC1SO6	16	19X29	1	.130
JMSO6-16RC2	M27500-16RC2SO6	16	19X29	2	.205
JMSO6-16RC3	M27500-16RC3SO6	16	19X29	3	.210
JMSO6-16RC4	M27500-16RC4SO6	16	19X29	4	.240
JMSO6-14RC1	M27500-14RC1SO6	14	19X27	1	.145
JMSO6-14RC2	M27500-14RC2SO6	14	19X27	2	.235
JMSO6-14RC3	M27500-14RC3SO6	14	19X27	3	.250
JMSO6-14RC4	M27500-14RC4SO6	14	19X27	4	.275
JMSO6-12RC1	M27500-12RC1SO6	12	19X25	1	.170
JMSO6-12RC2	M27500-12RC2SO6	12	19X25	2	.280
JMSO6-12RC3	M27500-12RC3SO6	12	19X25	3	.295
JMSO6-12RC4	M27500-12RC4SO6	12	19X25	4	.325

*CONSULT FACTORY FOR OTHER CODING AND NUMBER OF CONDUCTORS.