



# jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980  
 OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800  
 FAX 845-947-1712

## MULTI-CONDUCTOR CABLE - PVC

**DESCRIPTION:** MULTI-CONDUCTOR CABLE FOR USE IN CONTROL, AUDIO, AND COMPUTER CIRCUITS, AND SIMILAR APPLICATIONS. CABLES HAVE PVC COLOR CODED INSULATED CONDUCTORS. FOIL SHIELDED ITEMS HAVE A SUITABLE DRAIN WIRE AND FOIL WITH BRAID ITEMS HAVE A MINIMUM TINNED COPPER BRAID COVERAGE OF 65%. SUPPLIED WITH A GRAY PVC JACKET.

**SPECIFICATIONS:** UL, CSA AWM.




**CONDUCTOR:** STRANDED TINNED COPPER.

**INSULATION:** PVC.

**TEMPERATURE:** 80°C (90°C FOR CSA RATING).

**VOLTAGE:** AWG 24-16: 300 VOLTS.\*; AWG 14: 600 VOLTS RMS.

**ORDERING INFORMATION:** SPECIFY JAGUAR CATALOG NO.



NUMBER OF CONDUCTORS	UNSHIELDED	NOM O.D. (inches)	FOIL SHIELD	NOM O.D. (inches)	FOIL SHIELD + BRAID	NOM O.D. (inches)
<b># 24 AWG</b>						
2			JMFC24-02	.160	JMFB24-02	.180
3			JMFC24-03	.170	JMFB24-03	.190
4			JMFC24-04	.180	JMFB24-04	.210
6			JMFC24-06	.200	JMFB24-06	.230
7			JMFC24-07	.210	JMFB24-07	.240
8			JMFC24-08	.220	JMFB24-08	.250
10			JMFC24-10	.250	JMFB24-10	.270
15			JMFC24-15	.270	JMFB24-15	.300
20			JMFC24-20	.300	JMFB24-20	.330
25			JMFC24-25	.330	JMFB24-25	.360
30			JMFC24-30	.360	JMFB24-30	.380
40			JMFC24-40	.400	JMFB24-40	.430
50			JMFC24-50	.440	JMFB24-50	.460
60			JMFC24-60	.470	JMFB24-60	.500
<b># 22 AWG</b>						
2	JMUC22-02	.170	JMFC22-02	.180	JMFB22-02	.200
3	JMUC22-03	.190	JMFC22-03	.190	JMFB22-03	.210
4	JMUC22-04	.200	JMFC22-04	.200	JMFB22-04	.220
6	JMUC22-06	.230	JMFC22-06	.230	JMFB22-06	.250
7	JMUC22-07	.240	JMFC22-07	.240	JMFB22-07	.260
8	JMUC22-08	.250	JMFC22-08	.250	JMFB22-08	.270
10	JMUC22-10	.270	JMFC22-10	.280	JMFB22-10	.300
12	JMUC22-12	.286	JMFC22-12	.292	JMFB22-12	.312
15	JMUC22-15	.310	JMFC22-15	.310	JMFB22-15	.330
20	JMUC22-20	.350	JMFC22-20	.340	JMFB22-20	.360
25	JMUC22-25	.380	JMFC22-25	.380	JMFB22-25	.390
30	JMUC22-30	.410	JMFC22-30	.400	JMFB22-30	.420
40	JMUC22-40	.460	JMFC22-40	.450	JMFB22-40	.470
50	JMUC22-50	.500	JMFC22-50	.490	JMFB22-50	.510
60	JMUC22-60	.550	JMFC22-60	.530	JMFB22-60	.600