



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
 OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
 FAX 845-947-1712

MINIATURE CABLES

DESCRIPTION: SMALL CABLES DESIGNED FOR USE WHERE SPACE IS LIMITED OR CONCEALMENT IS REQUIRED, THESE CABLES ARE ALSO USED WHERE FLEXIBILITY IS NEEDED. APPLICATIONS INCLUDE USES SUCH AS FLOPPY DISK LEADS, HEAD CONNECTORS, GAME CONTROLS, AND SURVEILLANCE EQUIPMENT.

SPECIFICATIONS: UL-VW1 (STYLE 2879 32-24 AWG, OTHER STYLES AVAILABLE).

CONDUCTORS: STRANDED SOFT BARE OR TINNED COPPER.

TEMPERATURE RATING: 105°C (MUST BE DOWNRATED FOR SOME UL STYLES).

VOLTAGE RATING: #32 AWG 200 VOLTS; #30-20 AWG 600 VOLTS FOR INTERNAL EQUIPMENT USAGE (MUST BE DOWNRATED FOR UL STYLES).

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. & LIST UL STYLE IF UL LABELING IS REQUIRED.*

AWG	NO. OF STRANDS	NOM. O.D.	CABLED W/ JACKET	NOM. O.D.	TC BRAID SHIELD	NOM. O.D.	TC SPIRAL SHIELD & JACKET	NOM. O.D.	TC BRAID SHIELD & JACKET	NOM. O.D.		
SIZE	COND	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)		
32	7X40 TC	1			JFX-B132	.035			JFX-BJ132	.055		
32	7X40 TC	2	JFX-232	.046	JFX-J232	.064	JFX-B232	.058	JFX-SJ232	.070	JFX-BJ232	.076
32	7X40 TC	3	JFX-332	.050	JFX-J332	.068	JFX-B332	.062	JFX-SJ332	.074	JFX-BJ332	.080
32	7X40 TC	4	JFX-432	.055	JFX-J432	.073	JFX-B432	.067	JFX-SJ432	.079	JFX-BJ432	.085
32	7X40 TC	5	JFX-532	.057	JFX-J532	.075	JFX-B532	.069	JFX-SJ532	.081	JFX-BJ532	.087
30	7X38 TC	1			JFX-B130	.046	JFX-SJ130	.058	JFX-BJ130	.066		
30	7X38 TC	2	JFX-230	.060	JFX-J230	.080	JFX-B230	.076	JFX-SJ230	.088	JFX-BJ230	.096
30	7X38 TC	3	JFX-330	.066	JFX-J330	.086	JFX-B330	.082	JFX-SJ330	.094	JFX-BJ330	.102
30	7X38 TC	4	JFX-430	.072	JFX-J430	.092	JFX-B430	.088	JFX-SJ430	.100	JFX-BJ430	.108
29	51X46 BC	1			JSF-B129	.042			JSF-BJ129	.058		
29	51X46 BC	2	JSF-229	.060	JSF-J229	.076	JSF-B229	.072	JSF-SJ229	.082	JSF-BJ229	.088
29	51X46 BC	3	JSF-329	.066	JSF-J329	.083	JSF-B329	.078	JSF-SJ329	.088	JSF-BJ329	.094
28	7X36 TC	1			JFX-B128	.050	JFX-SJ128	.064	JFX-BJ128	.074		
28	7X36 TC	2	JFX-228	.068	JFX-J228	.089	JFX-B228	.088	JFX-SJ228	.099	JFX-BJ228	.109
28	7X36 TC	3	JFX-328	.075	JFX-J328	.096	JFX-B328	.095	JFX-SJ328	.106	JFX-BJ328	.116
28	7X36 TC	4	JFX-428	.082	JFX-J428	.103	JFX-B428	.102	JFX-SJ428	.113	JFX-BJ428	.123
26	7X34 TC	1			JFX-B126	.054	JFX-SJ126	.068	JFX-BJ126	.078		
26	7X34 TC	2	JFX-226	.076	JFX-J226	.099	JFX-B226	.096	JFX-SJ226	.109	JFX-BJ226	.119
26	7X34 TC	3	JFX-326	.084	JFX-J326	.107	JFX-B326	.104	JFX-SJ326	.117	JFX-BJ326	.127
26	7X34 TC	4	JFX-426	.091	JFX-J426	.114	JFX-B426	.111	JFX-SJ426	.124	JFX-BJ426	.134
26	66X44 BC	1			JSF-B126	.054	JSF-SJ126	.068	JSF-BJ126	.078		
26	66X44 BC	2	JSF-226	.084	JSF-J226	.109	JSF-B226	.104	JSF-SJ226	.119	JSF-BJ226	.129
26	66X44 BC	3	JSF-326	.092	JSF-J326	.117	JSF-B326	.112	JSF-SJ326	.127	JSF-BJ326	.137
26	66X44 BC	4	JSF-426	.100	JSF-J426	.125	JSF-B426	.120	JSF-SJ426	.135	JSF-BJ426	.145
24	7X32 TC	1			JFX-B124	.060	JFX-SJ124	.075	JFX-BJ124	.085		
24	7X32 TC	2	JFX-224	.088	JFX-J224	.121	JFX-B224	.108	JFX-SJ224	.131	JFX-BJ224	.141
24	7X32 TC	3	JFX-324	.096	JFX-J324	.125	JFX-B324	.116	JFX-SJ324	.135	JFX-BJ324	.145
24	105X44 BC	1			JSF-B124	.058	JSF-SJ124	.073	JSF-BJ124	.083		
24	105X44 BC	2	JSF-224	.092	JSF-J224	.122	JSF-B224	.112	JSF-SJ224	.132	JSF-BJ224	.142
24	105X44 BC	3	JSF-324	.097	JSF-J324	.127	JSF-B324	.117	JSF-SJ324	.137	JSF-BJ324	.147
22	7X30 TC	1			JFX-B122	.067	JFX-SJ122	.082	JFX-BJ122	.092		
22	7X30 TC	2	JFX-222	.102	JFX-J222	.132	JFX-B222	.122	JFX-SJ222	.142	JFX-BJ222	.152
22	7X30 TC	3	JFX-322	.112	JFX-J322	.142	JFX-B322	.132	JFX-SJ322	.152	JFX-BJ322	.162
22	168X44 BC	1			JSF-B122	.068	JSF-SJ122	.082	JSF-BJ122	.092		
22	168X44 BC	2	JSF-222	.106	JSF-J222	.136	JSF-B222	.126	JSF-SJ222	.146	JSF-BJ222	.156
22	168X44 BC	3	JSF-322	.117	JSF-J322	.147	JSF-B322	.137	JSF-SJ322	.157	JSF-BJ322	.167
20	10X30 TC	1			JFX-B120	.079	JFX-SJ120	.092	JFX-BJ120	.102		
20	10X30 TC	2	JFX-220	.122	JFX-J220	.152	JFX-B220	.142	JFX-SJ220	.162	JFX-BJ220	.172
20	10X30 TC	3	JFX-320	.134	JFX-J320	.164	JFX-B320	.154	JFX-SJ320	.174	JFX-BJ320	.184
20	266X44 BC	1			JSF-B120	.080	JSF-SJ120	.092	JSF-BJ120	.102		
20	266X44 BC	2	JSF-220	.126	JSF-J220	.156	JSF-B220	.146	JSF-SJ220	.166	JSF-BJ220	.176
20	266X44 BC	3	JSF-320	.138	JSF-J320	.168	JSF-B320	.158	JSF-SJ320	.178	JSF-BJ320	.188

*OTHER CONFIGURATIONS AVAILABLE, CONSULT FACTORY.