



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

TYPE-C PVC INSULATED WIRE

DESCRIPTION: MEDIUM WALL GENERAL PURPOSE ELECTRONIC HOOK-UP WIRE RESISTANT TO WATER, OIL, ACIDS, SOLVENTS & FUNGUS. FLAME RETARDED.

MIL. SPEC. NO.: MIL-W-16878/2.

CONDUCTOR: STRANDED OR SOLID TINNED COPPER.

INSULATION: PVC, .016".

TEMPERATURE RATING: -55°C TO 105°C.

VOLTAGE RATING: 1000 VOLTS R.M.S.

STANDARD SPOOL PUT-UP: 1000 FT., 5000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION		TINNED COPPER CONDUCTOR		O.D. (inches)	
	MIL-W-16878D	MIL-W-16878/2	AWG SIZE	STRAND	MIN.	MAX.
JC2601	C26 (1)	BDA	26	SOLID	.046	.054
JC2607	C26 (7)	BDB	26	7X34	.049	.057
JC2619	C26 (19)	BDE	26	19X38	.049	.057
JC2401	C24 (1)	BEA	24	SOLID	.050	.058
JC2407	C24 (7)	BEB	24	7X32	.054	.062
JC2419	C24 (19)	BEE	24	19X36	.054	.062
JC2201	C22 (1)	BFA	22	SOLID	.055	.064
JC2207	C22 (7)	BFB	22	7X30	.060	.068
JC2219	C22 (19)	BFE	22	19X34	.060	.068
JC2001	C20 (1)	BGA	20	SOLID	.062	.070
JC2007	C20 (7)	BGB	20	7X28	.068	.076
JC2010	C20 (10)	BGC	20	10X30	.068	.076
JC2019	C20 (19)	BGE	20	19X32	.068	.076
JC1801	C18 (1)	BHA	18	SOLID	.070	.079
JC1807	C18 (7)	BHB	18	7X26	.079	.087
JC1816	C18 (16)	BHD	18	16X30	.077	.085
JC1819	C18 (19)	BHE	18	19X30	.079	.087
JC1601	C16 (1)	BJA	16	SOLID	.080	.089
JC1619	C16 (19)	BJE	16	19X29	.089	.097
JC1626	C16 (26)	BJF	16	26X30	.092	.100
JC1401	C14 (1)	BKA	14	SOLID	.094	.102
JC1419	C14 (19)	BKE	14	19X27	.102	.110
JC1441	C14 (41)	BKH	14	41X30	.110	.118
JC1201	C12 (1)	BLA	12	SOLID	.110	.119
JC1219	C12 (19)	BLE	12	19X25	.121	.129
JC1237	C12 (37)	BLG	12	37X28	.119	.127
JC1265	C12 (65)	BLJ	12	65X30	.128	.136