



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

TYPE-D PVC INSULATED WIRE

DESCRIPTION: HEAVY WALL GENERAL PURPOSE ELECTRONIC HOOK-UP WIRE. RESISTANT TO WATER, OIL, ACIDS, SOLVENTS & FUNGUS. FLAME RETARDED.

MIL. SPEC. NO.: MIL-W-16878/3.

CONDUCTOR: STRANDED OR SOLID TINNED COPPER.

INSULATION: PVC, .030".

TEMPERATURE RATING: -55°C TO 105°C.

VOLTAGE RATING: 3000 VOLTS R.M.S.

STANDARD SPOOL PUT-UP: 1000 FT., 5000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION		TINNED COPPER CONDUCTOR		O.D. (inches)	
	MIL-W-16878D	MIL-W-16878/3	AWG SIZE	STRAND	MIN.	MAX.
JD2401	D24 (1)	BEA	24	SOLID	.071	.086
JD2407	D24 (7)	BEB	24	7X32	.075	.090
JD2419	D24 (19)	BEE	24	19X36	.075	.090
JD2201	D22 (1)	BFA	22	SOLID	.075	.091
JD2207	D22 (7)	BFB	22	7X30	.081	.096
JD2219	D22 (19)	BFE	22	19X34	.081	.096
JD2001	D20 (1)	BGA	20	SOLID	.083	.098
JD2007	D20 (7)	BGB	20	7X28	.089	.104
JD2019	D20 (19)	BGE	20	19X32	.089	.104
JD1801	D18 (1)	BHA	18	SOLID	.091	.106
JD1807	D18 (7)	BHB	18	7X26	.100	.115
JD1819	D18 (19)	BHE	18	19X30	.100	.115
JD1601	D16 (1)	BJA	16	SOLID	.102	.117
JD1619	D16 (19)	BJE	16	19X29	.110	.125
JD1626	D16 (26)	BJF	16	26X30	.113	.128
JD1401	D14 (1)	BKA	14	SOLID	.115	.130
JD1419	D14 (19)	BKE	14	19X27	.123	.138
JD1441	D14 (41)	BKH	14	41X30	.131	.146
JD1201	D12 (1)	BLA	12	SOLID	.145	.159
JD1219	D12 (19)	BLE	12	19X25	.156	.171
JD1237	D12 (37)	BLG	12	37X28	.153	.168
JD1265	D12 (65)	BLJ	12	65X30	.162	.177
JD1001	D10 (1)	BMA	10	SOLID	.166	.181
JD1037	D10 (37)	BMG	10	37X26	.175	.190
JD10105	D10 (105)	BMK	10	105X30	.191	.206
JD08133	D8 (133)	BNL	8	133X29	.241	.256
JD06133	D6 (133)	BPL	6	133X27	.286	.301
JD04133	D4 (133)	BRL	4	133X25	.348	.368
JD02665	D2 (665)	BSP	2	665X30	.422	.442
JD01817	D1 (817)	BTR	1	817X30	.472	.492
JDX01045	D0 (1045)	BUS	0	1045X30	.525	.545