



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712

TYPE-LW PVC INSULATED WIRE

DESCRIPTION: THIN WALL GENERAL PURPOSE ELECTRONIC HOOK-UP WIRE RESISTANT TO WATER, OIL, ACIDS, SOLVENTS & FUNGUS. FLAME RETARDED.

MIL. SPEC. NO.: MIL-W-76D, TYPE LW.

CONDUCTOR: STRANDED OR SOLID TINNED COPPER.

INSULATION: PVC, .010".

TEMPERATURE RATING: -55°C TO 90°C.

VOLTAGE RATING: 300 VOLTS R.M.S. (420 VOLTS D. C.).

STANDARD SPOOL PUT-UP: 1000 FT., 5000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR CODE.

CATALOG NO.	MILITARY DESIGNATION MIL-W-76D, TYPE LW	TINNED COPPER CONDUCTOR		O.D. (inches)	
		AWG SIZE	STRAND	MIN.	MAX.
JLW3001	M76-LW-C-30-1-A-*	30	SOLID	.026	.033
JLW3007	M76-LW-C-30-7-A-*	30	7X38	.028	.037
JLW3010	M76-LW-C-30-10-A-*	30	10X40	.028	.037
JLW2801	M76-LW-C-28-1-A-*	28	SOLID	.028	.037
JLW2807	M76-LW-C-28-7-A-*	28	7X36	.031	.039
JLW2816	M76-LW-C-28-16-A-*	28	16X40	.031	.039
JLW2819	M76-LW-C-28-19-A-*	28	19X40	.031	.039
JLW2601	M76-LW-C-26-1-A-*	26	SOLID	.032	.040
JLW2607	M76-LW-C-26-7-A-*	26	7X34	.035	.043
JLW2619	M76-LW-C-26-19-A-*	26	19X38	.035	.043
JLW2626	M76-LW-C-26-26-A-*	26	26X40	.035	.043
JLW2401	M76-LW-C-24-1-A-*	24	SOLID	.036	.044
JLW2407	M76-LW-C-24-7-A-*	24	7X32	.040	.049
JLW2419	M76-LW-C-24-19-A-*	24	19X36	.040	.049
JLW2441	M76-LW-C-24-41-A-*	24	41X40	.040	.049
JLW2201	M76-LW-C-22-1-A-*	22	SOLID	.041	.049
JLW2207	M76-LW-C-22-7-A-*	22	7X30	.046	.057
JLW2219	M76-LW-C-22-19-A-*	22	19X34	.046	.057
JLW2266	M76-LW-C-22-66-A-*	22	66X40	.046	.057
JLW2001	M76-LW-C-20-1-A-*	20	SOLID	.046	.056
JLW2007	M76-LW-C-20-7-A-*	20	7X28	.054	.065
JLW2010	M76-LW-C-20-10-A-*	20	10X30	.054	.065
JLW2019	M76-LW-C-20-19-A-*	20	19X32	.054	.065
JLW20105	M76-LW-C-20-105-A-*	20	105X40	.054	.065

*DENOTES COLOR CODE.