



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
 OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
 FAX 845-947-1712

PTFE TUBING JT-200, JT-250, JT-400

DESCRIPTION: JAGUAR JT-200, JT-250, AND JT-400 ARE NON-SHRINKABLE EXTRUDED PTFE TUBINGS DESIGNED TO OPERATE UNDER EXTREME ENVIRONMENTAL CONDITIONS. THEY ARE CHEMICALLY INERT AND MAINTAIN FLEXIBILITY THROUGHOUT THEIR ENTIRE OPERATING TEMPERATURE RANGE.

SPECIFICATIONS: UL-224; JT-250 AMS 3653, MIL-1-22129; JT-200 AMS 3655; JT-400 AMS 3654.

MATERIAL: POLYTETRAFLUOROETHYLENE.

TEMPERATURE RATING: -65°C TO 260°C.

STANDARD COLOR: TRANSLUCENT WHITE (NATURAL). TEN RETMA (EIA) COLORS AVAILABLE.

PACKAGING: REELS OR COILS. SIZES ABOVE 3/4" (.750") ARE SUPPLIED IN CUT LENGTHS.*

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO., INCLUDING WALL TYPE, AWG SIZE NO., AND COLOR. EXAMPLE: JT-250-1/8 NATURAL.

JAGUAR JT-250 STANDARD WALL

JAGUAR JT-200 THIN WALL

JAGUAR JT-400 LIGHT WALL

ORDER AS SIZE NO.	NOMINAL I.D. (in.)	NOMINAL WALL (in.)	NOMINAL O.D. (in.)	ORDER AS SIZE NO.	NOMINAL I.D. (in.)	NOMINAL WALL (in.)	NOMINAL O.D. (in.)	ORDER AS SIZE NO.	NOMINAL I.D. (in.)	NOMINAL WALL (in.)	NOMINAL O.D. (in.)
30	0.012	0.009	0.030	30	0.012	0.009	0.030	30	0.012	0.006	0.024
28	0.015	0.009	0.033	28	0.015	0.009	0.033	28	0.015	0.006	0.027
26	0.018	0.009	0.036	26	0.018	0.009	0.036	26	0.018	0.006	0.030
24	0.022	0.012	0.046	24	0.022	0.010	0.042	24	0.022	0.006	0.034
23	0.026	0.012	0.050	23	0.026	0.010	0.046	23	0.026	0.006	0.038
22	0.028	0.012	0.052	22	0.028	0.010	0.048	22	0.028	0.006	0.040
21	0.032	0.012	0.056	21	0.032	0.010	0.052	21	0.032	0.006	0.044
20	0.034	0.016	0.066	20	0.034	0.012	0.058	20	0.034	0.006	0.046
19	0.038	0.016	0.070	19	0.038	0.012	0.062	19	0.038	0.006	0.050
18	0.042	0.016	0.074	18	0.042	0.012	0.066	18	0.042	0.006	0.054
17	0.047	0.016	0.079	17	0.047	0.012	0.071	17	0.047	0.006	0.059
16	0.053	0.016	0.085	16	0.053	0.012	0.077	16	0.053	0.006	0.065
15	0.059	0.016	0.091	15	0.059	0.012	0.083	15	0.059	0.006	0.071
14	0.066	0.016	0.098	14	0.066	0.012	0.090	14	0.066	0.008	0.082
13	0.076	0.016	0.108	13	0.076	0.012	0.100	13	0.076	0.008	0.092
12	0.085	0.016	0.117	12	0.085	0.012	0.109	12	0.085	0.008	0.101
11	0.095	0.016	0.127	11	0.095	0.012	0.119	11	0.095	0.008	0.111
10	0.106	0.016	0.138	10	0.106	0.012	0.130	10	0.106	0.008	0.122
9	0.118	0.020	0.158	9	0.118	0.015	0.148	9	0.118	0.008	0.134
1/8	0.130	0.020	0.170	1/8	0.130	0.015	0.160	1/8	0.130	0.008	0.146
8	0.133	0.020	0.173	8	0.133	0.015	0.163	8	0.133	0.008	0.149
7	0.148	0.020	0.188	7	0.148	0.015	0.178	7	0.148	0.008	0.164
6	0.166	0.020	0.206	6	0.166	0.015	0.196	6	0.166	0.010	0.186
5	0.186	0.020	0.226	5	0.186	0.015	0.216	5	0.186	0.010	0.206
3/16	0.192	0.020	0.232	3/16	0.192	0.015	0.222	3/16	0.192	0.010	0.212
4	0.208	0.020	0.248	4	0.208	0.015	0.238	4	0.208	0.010	0.228
3	0.234	0.020	0.274	3	0.234	0.015	0.264	3	0.234	0.010	0.254
1/4	0.255	0.020	0.295	1/4	0.255	0.015	0.285	1/4	0.255	0.010	0.275
2	0.263	0.020	0.303	2	0.263	0.015	0.293	2	0.263	0.010	0.283
1	0.294	0.020	0.334	1	0.294	0.015	0.324	1	0.294	0.010	0.314
5/16	0.321	0.020	0.361	5/16	0.321	0.015	0.351	5/16	0.321	0.012	0.345
0	0.330	0.020	0.370	0	0.330	0.015	0.360	0	0.330	0.012	0.354
3/8	0.387	0.025	0.437	3/8	0.387	0.015	0.417	3/8	0.387	0.015	0.417
7/16	0.451	0.025	0.501	7/16	0.451	0.018	0.487	7/16	0.451	0.018	0.487
1/2	0.515	0.025	0.565	1/2	0.515	0.018	0.551	1/2	0.515	0.018	0.551
5/8	0.643	0.025	0.693	5/8	0.643	0.020	0.683	5/8	0.643	0.020	0.683
3/4	0.772	0.030	0.832	3/4	0.772	0.025	0.822	3/4	0.772	0.020	0.812
7/8	0.902	0.035	0.972								
1.0	1.030	0.035	1.100								
1-1/4	1.287	0.040	1.367								
1-1/2	1.550	0.045	1.640								

*ALSO AVAILABLE AS CUT PIECES, CONSULT FACTORY.