



jaguar industries inc

• WIRE • CABLE • TUBING

380 ROUTE 210, P.O. BOX 444 STONY POINT, N.Y. 10980
OUTSIDE NEW YORK STATE CALL TOLL FREE 1-800-443-6528

845-947-1800
FAX 845-947-1712


STYLES 1015, 1028, & 1283, MTW, CSA TEW

DESCRIPTION: HEAVY WALL PVC INSULATED GENERAL PURPOSE ELECTRONIC HOOK-UP WIRE RESISTANT TO WATER, OIL, ACIDS, SOLVENTS, AND FUNGUS. DESIGNED FOR USE AS INTERNAL WIRING OF APPLIANCES. MTW RATED AS MACHINE TOOL WIRE FOR APPROPRIATE SIZES.

SPECIFICATIONS: UL-VW1 (STYLE 1015 AWG 30-6; STYLE 1028 AWG 22-8; STYLE 1283 AWG 8,6); CSA TEW.



CONDUCTOR: STRANDED OR SOLID TINNED COPPER.*

TEMPERATURE RATING: 105°C.

VOLTAGE RATING: 600 VOLTS R.M.S. ( 2500 VOLTS PEAK, FOR ELECTRONIC USE ONLY).

STANDARD SPOOL PUT-UP: 1000 FT. 5000 FT.

ORDERING INFORMATION: SPECIFY JAGUAR CATALOG NO. AND COLOR.

| AWG SIZE | STRAND |  STYLE 1015 | | |  STYLE 1028 | | |
|-------------|--------|--|------------|------------|--|------------|------------|
| | | CATALOG # | WALL (in.) | O.D. (in.) | CATALOG # | WALL (in.) | O.D. (in.) |
| 30 | SOLID | J5UL3001 | .030 | .071 | | | |
| 30 | 7X38 | J5UL3007 | .030 | .073 | | | |
| 28 | SOLID | J5UL2801 | .030 | .074 | | | |
| 28 | 7X36 | J5UL2807 | .030 | .076 | | | |
| 26 | SOLID | J5UL2601 | .030 | .077 | | | |
| 26 | 7X34 | J5UL2607 | .030 | .080 | | | |
| 24 | SOLID | J5UL2401 | .030 | .081 | | | |
| 24 | 7X32 | J5UL2407 | .030 | .085 | | | |
| 22 | SOLID | J5UL2201 | .030 | .092 | | | |
| 22 | 7X30 | J5UL2207 | .030 | .091 | J8UL2207 | .045 | .121 |
| 20 | SOLID | J5UL2001 | .030 | .093 | J8UL2001 | .045 | .123 |
| 20 | 10X30 | J5UL2010 | .030 | .099 | J8UL2010 | .045 | .129 |
| 18 | SOLID | J5UL1801 | .030 | .101 | J8UL1801 | .045 | .131 |
| 18 | 16X30 | J5UL1816 | .030 | .110 | J8UL1816 | .045 | .140 |
| 16 | SOLID | J5UL1601 | .030 | .111 | J8UL1601 | .045 | .141 |
| 16 | 26X30 | J5UL1626 | .030 | .121 | J8UL1626 | .045 | .151 |
| 14 | SOLID | J5UL1401 | .030 | .125 | J8UL1401 | .045 | .155 |
| 14 | 41X30 | J5UL1441 | .030 | .133 | J8UL1441 | .045 | .163 |
| 12 | SOLID | J5UL1201 | .030 | .142 | J8UL1201 | .045 | .172 |
| 12 | 65X30 | J5UL1265 | .030 | .148 | J8UL1265 | .045 | .178 |
| 10 | 105X30 | J5UL10105 | .030 | .172 | J8UL10105 | .045 | .202 |
| 8 | 133X29 | J5UL08133 | .045 | .250 | J8UL08133 | .045 | .250 |
| 6 | 133X27 | J5UL06133 | .060 | .325 | | | |

STYLE 1283

| | | | | |
|---|--------|-----------|------|------|
| 8 | 133X29 | J3UL08133 | .060 | .300 |
| 6 | 133X27 | J3UL06133 | .060 | .325 |

*BARE COPPER AND ADDITIONAL STRANDINGS AVAILABLE, CONSULT FACTORY.